LGAI Technological Center, S.A. Campus UAB - Ronda de la Font del Carme s/n E-08193 Bellaterra (Barcelona) T +34 93 567 20 00 F +34 93 567 20 01 www.applus.com



CERTIFICATE

No.

UAE-296

PRODUCT APPROVAL CERTIFICATE FOR THE UNITED ARAB EMIRATES

LGAI TECHNOLOGICAL CENTER S.A. certifies the following:

TEST REPORT NUMBER:	16/12372-936 Part 1 and 2	CERTIFICATE NUMBER:	UAE- 296
DATE OF ISSUE:	19/05/2016	DATE OF ISSUE:	30/05/2016
DATE OF EXPIRY:		DATE OF EXPIRY:	30/05/2017

FACTORY/ MANUFACTURER:	GAMMASTONE S.r.I.	BRAND/S:	GAMMASTONE
ADRESS/ REGION:	GAMMASTONE S.r.I. Rignano Flaminio (RM) Via Flaminia n. 148 ITALY	MODEL:	GRES AIR
		LOGO ON THE PRODUCT:	■ GammaStone Architectural & Diesign Evolutions

	DATA FROM TEST REPORT:	
PRODUCT DETAILS:	Panel made up of a sheet of porcelain-finished gres, a foam core interposed between to mats of fiberglass and a sheet of stainless steel, with commercial reference "GAMMASTONE GRES AIR".	
TEST STANDARD:	EN-ISO 11925-2:2005: Flammability when subjected to direct impingement. Test on a single source of flame.	
	EN 13823:2010+A1:2014: Reaction to fire tests for building products - Building products excluding floorings exposed to the thermal attack by a single burning item.	
TEST DESCRIPTION:	EN-ISO 11925-2:2005: Application of a flame for 30 seconds and observation for another 30 seconds of the flame propagation and the dripping of flammable material, both on the surface and on the edge. EN 13823:2010+A1:2014: Application of a 30 kW flame to the test specimen, and for 30 minute the oxygen consumption and CO2 production are measured in order to calculate all the parameters.	
SPECIFICATION OF TEST SPECIMEN:	«GAMMASTONE GRES AIR» test specimen with the following characteristics: Thickness: 15 mm. Mass per unit area: 15 kg/m2. Stainless Steel sheet characteristics: thickness 0.5 mm and weight 3 kg/m3.	